






20' X 40' RECTANGLE 2' RADIUS



- 8' COZYCOVE (Optional)**
 -2 6' PANELS
 +2 2' PANELS
 +1 BRACE
 +1 8' COZY COVE



GENERAL NOTES

1. These are finished dimensions ready for the liner.
2. Dimensions are from inside pool panels.
3. The ideal water level should be to the middle of the skimmer opening(s).

EXCAVATION NOTES

1. Rough excavation should be 2" deeper in each instance.
2. Soil to have minimum bearing capacity of 2000 P.S.F.
3. Locate top of pool at least 6" above surrounding land elevation.
4. See Overlay Detail for excavation around pool.
5. Fill voids under base of panels and ramp well.
6. Backfill with non-expansive material.


ADDITIONAL NOTES

THIS DOCUMENT IS FOR ILLUSTRATIVE PURPOSES ONLY. The dealer or contractor who sells or installs your pool is an independent contractor and is not an agent of the Manufacturer. The construction methods illustrated here are suggestions and apply only to normal ground conditions. There may be additional precautions and/or methods of construction. Proper installation is the responsibility of the dealer/builder/contractor.

DIMENSIONS

Label	Value
A	20'
B	40'
D	34"
E	5'
F	84"
G	10'
H	5'
I	5'
J	5'
K	7'
L	15'
M	13'
M2	-
T	-
S	-
N	-
P	-
U	-


APSP TYPE	III	SQ. FOOTAGE	800
PERIMETER	116'7"	GALLONS	28004



BILL OF MATERIALS


QTY	PART	DESCRIPTION
11	HP506	6' PANEL
1	HP506L	6' PANEL (LIGHT)
2	HP506A	6' PANEL (A/G)
4	HP505	5' PANEL
4	HP352M	2'R PANEL
22	HP599	BRACE

OVERDIG DETAIL



*NOTE: REFER TO INSTALLATION MANUAL FOR MORE INFO.

COPING LAYOUT



NO DIVING WARNING


ATTENTION DEALER/BUILDER: It is your responsibility to ensure the safety package provided is delivered to the pool owner and that the "NO DIVING" labels are properly installed.

NO DIVING WARNING LABELS MUST BE INSTALLED IN NO DIVING AREAS ACCORDING TO APSP SPECIFICATIONS

A DANGER
 NO DIVING
 SHALLOW WATER
 DIVING MAY CAUSE DEATH OR PERMANENT INJURY

* SUGGESTED LABEL LOCATIONS ARE SPECIFIED IN THE COPING LAYOUT

PRE-CUT PANEL LEGEND



GENERAL NOTES

1. These are finished dimensions ready for the liner.
2. Dimensions are from inside pool panels.
3. The ideal water level should be to the middle of the skimmer opening(s).

EXCAVATION NOTES

1. Rough excavation should be 2" deeper in each instance.
2. Soil to have minimum bearing capacity of 2000 P.S.F.
3. Locate top of pool at least 6" above surrounding land elevation.
4. See Overlay Detail for excavation around pool.
5. Fill voids under base of panels and ramp well.
6. Backfill with non-expansive material.

ADDITIONAL NOTES

THIS DOCUMENT IS FOR ILLUSTRATIVE PURPOSES ONLY. The dealer or contractor who sells or installs your pool is an independent contractor and is not an agent of the Manufacturer. The construction methods illustrated here are suggestions and apply only to normal ground conditions. There may be additional precautions and/or methods of construction. Proper installation is the responsibility of the dealer/builder/contractor.

DATE: JAN 2007
 PANEL LINE: PINNACLE
 DRAWING TITLE: 20' X 40' RECTANGLE 2' RADIUS
 DRAWING NUMBER: 50163

543 South Main Street - Sweetwater, TN 37874