


20' X 40' RECTANGLE 4' RADIUS


39



DIMENSIONS

Label	Value
A	20'
B	40'
D	34"
E	5'
F	84"
G	10'
H	5'
I	5'
J	5'
K	7'
L	15'
M	13'
M2	-
T	-
S	-
N	-
P	-
U	-


APSP TYPE	III	SQ. FOOTAGE	800
PERIMETER	113'2"	GALLONS	27642




BILL OF MATERIALS

QTY	PART	DESCRIPTION
8	HP506	6' PANEL
2	HP506A	6' PANEL (AVG)
6	HP504	4' PANEL
1	HP504L	4' PANEL (LIGHT)
8	HP354	4'R PANEL
25	HP599	BRACE

OVERDIG DETAIL



COPING LAYOUT



GENERAL NOTES


- These are finished dimensions ready for the liner.
- Dimensions are from inside pool panels.
- The ideal water level should be to the middle of the skimmer opening(s).

EXCAVATION NOTES

- Rough excavation should be 2" deeper in each instance.
- Soil to have minimum bearing capacity of 2000 P.S.F.
- Locate top of pool at least 6" above surrounding land elevation.
- See Overdig Detail for excavation around pool.
- Fill voids under base of panels and ramp well.
- Backfill with non-expansive material.

ADDITIONAL NOTES

THIS DOCUMENT IS FOR ILLUSTRATIVE PURPOSES ONLY. The dealer or contractor who sells or installs your pool is an independent contractor and is not an agent of the Manufacturer. The construction methods illustrated here are suggestions and apply only to normal ground conditions. There may be additional precautions and/or methods of construction. Proper installation is the responsibility of the dealer/builder/contractor.



PRE-CUT PANEL LEGEND

*** SUGGESTED LABEL LOCATIONS ARE SPECIFIED IN THE COPING LAYOUT**

A DANGER NO DIVING SHALLOW WATER DIVING MAY CAUSE DEATH OR PERMANENT INJURY



543 South Main Street - Sweetwater, TN 37874

DATE	PANEL LINE	DRAWING TITLE	DRAWING NUMBER
JAN 2007	PINNACLE	20' X 40' RECTANGLE 4' RADIUS	50166